

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170811-E155795  
**Report Reference** E155795-20031106  
**Issue Date** 2017-AUGUST-11

**Issued to:** EUCHNER GMBH + CO KG  
POSTFACH 10 01 52  
LEINFELDEN  
70745 ECHTERDINGEN GERMANY

**This is to certify that representative samples of** SWITCHES, INDUSTRIAL CONTROL  
See Addendum Page for Models

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL508, Industrial Control Equipment  
CSA C22.2 No. 14-13, Industrial Control Equipment

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170811-E155795  
**Report Reference** E155795-20031106  
**Issue Date** 2017-AUGUST-11

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open Type Models ESM- followed by BL201, BL202, BL203 may be followed by P; Models ESM- followed by BA201A, BA202A, BA203A; Models ESM- followed by BA201, BA202, BA203 may be followed by P; Models ESM- followed by BA301, BA302, BA303 may be followed by P; Models ESM- followed by BA301A; Models ESM- followed by ES301, ES302, ES303 may be followed by P; Models ESM- followed by TE301, TE302, TE303 may be followed by P; Models ESM- followed by TE301 may be followed by P, followed by -05S; Models ESM- followed by BT421, BT411, BT401 may be followed by P; Models ESM- followed by BT421, BT411, BT401 may be followed by P, followed by -20S or -50s; Models ESM- followed by BA701 may be followed by P.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

